

TECHNISCHE DATEN:

Aufbau

Hutmutter	Messing CuZn39Pb3, galv. vernickelt
Dichteinsatz	TPE, farblich codiert
Zwischenstutzen	Messing CuZn39Pb3, galv. vernickelt
O-Ring	Nitrilkautschuk NBR
Anschlussgewinde	metrisch, nach EN 60423

Eigenschaften

- mehrere, farblich codierte Dichteinsätze pro Größe
- großflächige Kabelabdichtung
- montagefreundlich

Temperaturbereich	-40 °C / +130 °C
Schutzart	IP68 - 5 bar

TECHNICAL DATA:


Configuration

Dome nut	Brass CuZn39Pb3, nickel-plated
Sealing insert	TPE, colour coded
Gland body	Brass CuZn39Pb3, nickel-plated
O-ring	Nitrile rubber NBR
Connecting thread	metric, as per EN 60423

Properties

- different colour coded sealing inserts for each size
- large surface sealant for the cable
- easy-to-install

Temperature range	-40 °C / +130 °C
Protection grade	IP68 - 5 bar




Merkmale

Characteristics

Anschlussgewinde Standardlänge

Connecting thread standard length

A	øC mm	$\frac{H}{mm}$ L mm	SW1 mm	SW2 mm	H mm		Art.-Nr. / Part No.
M12x1,5	4 - 6,5	5	14	14	25	50	18M120465
M16x1,5	4 - 6,5	6	18	17	26	50	18M160465
M16x1,5	5 - 8	6	18	17	26	50	18M160508
M16x1,5	6,5 - 9,5	6	18	17	26	50	18M166595
M20x1,5	4 - 6,5	6	22	22	26,5	50	18M200465
M20x1,5	5 - 8	6	22	22	26,5	50	18M200508
M20x1,5	6,5 - 9,5	6	22	22	26,5	50	18M206595
M20x1,5	7 - 10,5	6	22	22	26,5	50	18M200710
M20x1,5	9 - 13	6,5	22	22	26,5	50	18M200913
M25x1,5	4,5 - 6,5	6,5	28	24	28,5	50	18M250465
M25x1,5	5 - 8	6,5	28	24	28,5	50	18M250508
M25x1,5	6,5 - 9,5	6,5	28	24	28,5	50	18M256595
M25x1,5	7 - 10,5	6,5	28	24	28,5	50	18M250710
M25x1,5	9 - 13	6,5	28	24	28,5	50	18M250913
M25x1,5	11,5 - 15,5	6,5	28	24	28,5	50	18M251115
M32x1,5	7 - 10,5	7	35	30	33	25	18M320710
M32x1,5	9 - 13	7	35	30	33	25	18M320913
M32x1,5	11,5 - 15,5	7	35	30	33	25	18M321115
M32x1,5	14 - 18	7	35	30	33	25	18M321418
M32x1,5	17 - 20,5	7	35	30	33	25	18M321721
M40x1,5	11,5 - 15,5	8	43	40	33	10	18M401115
M40x1,5	14 - 18	8	43	40	33	10	18M401418
M40x1,5	17 - 20,5	8	43	40	33	10	18M401721
M40x1,5	20 - 25	8	43	40	33	10	18M402025
M40x1,5	24 - 28	8	43	40	33	10	18M402428
M50x1,5	27 - 32	9	54	50	38	5	18M502732