

## Han Q 5/0-M-c with coding



Image is for illustration purposes only. Please refer to product description.

|                    |   |
|--------------------|---|
| Part number        | 09 12 005 3004  |
| Specification      | Han Q 5/0-M-c with coding   |
| HARTING eCatalogue | <a href="https://b2b.harting.com/09120053004">https://b2b.harting.com/09120053004</a> |

### Identification

|                |                    |
|----------------|--------------------|
| Category       | Inserts            |
| Series         | Han <sup>®</sup> Q |
| Identification | 5/0                |

### Version

|                    |   |
|--------------------|---|
| Termination method | Crimp termination   |
| Gender             | Male  |
| Size               | 3 A   |
| Number of contacts | 5   |
| PE contact         | Yes   |
| Details            | Please order crimp contacts separately.<br>Please order coding pins separately. |

### Technical characteristics

|                                   |                              |
|-----------------------------------|------------------------------|
| Conductor cross-section           | 0.14 ... 2.5 mm <sup>2</sup> |
| Rated current                     | 16 A                         |
| Rated voltage conductor-earth     | 230 V                        |
| Rated voltage conductor-conductor | 400 V                        |
| Rated impulse voltage             | 4 kV                         |
| Pollution degree                  | 3                            |
| Rated voltage acc. to UL          | 600 V                        |
| Rated voltage acc. to CSA         | 600 V                        |
| Insulation resistance             | >10 <sup>10</sup> Ω          |



Pushing Performance  
Since 1945

## Technical characteristics

|                      |                 |
|----------------------|-----------------|
| Limiting temperature | -40 ... +125 °C |
| Mating cycles        | ≥500            |

## Material properties

|   |  |
|---|--|
| Material (insert)                         | Polycarbonate (PC)                                     |
| Colour (insert)                           | RAL 7032 (pebble grey)                                 |
| Material flammability class acc. to UL 94 | V-0  |
| RoHS                                      | compliant with exemption                               |
| RoHS exemptions                           | 6(c): Copper alloy containing up to 4 % lead by weight |
| ELV status                                | compliant with exemption                               |
| China RoHS                                | 50   |
| REACH Annex XVII substances               | Not contained  |
| REACH ANNEX XIV substances                | Not contained  |
| REACH SVHC substances                     | Yes  |
| REACH SVHC substances                     | Lead   |
| ECHA SCIP number                          | 5dbb3851-b94e-4e88-97a1-571845975242                   |
| California Proposition 65 substances      | Yes  |
| California Proposition 65 substances      | Lead<br>Nickel<br>Naphthalene                          |
| Fire protection on railway vehicles       | EN 45545-2 (2020-08)                                   |
| Requirement set with Hazard Levels        | R22 (HL 1-3)<br>R23 (HL 1-3)                           |

## Specifications and approvals

|                |  |
|----------------|--|
| Specifications | IEC 60664-1<br>IEC 61984                                   |
| UL / CSA       | UL 1977 ECBT2.E235076<br>CSA-C22.2 No. 182.3 ECBT8.E235076 |
| Approvals      | DNV GL   |

## Commercial data

|                                |          |
|--------------------------------|----------|
| Packaging size                 | 10       |
| Net weight                     | 12.83 g  |
| Country of origin              | Romania  |
| European customs tariff number | 85366990 |



**Pushing Performance**  
Since 1945

## Commercial data

|        |   |
|--------|---|
| GTIN   | 5713140162396                                     |
| ETIM   | EC000438  |
| eCl@ss | 27440205 Contact insert for industrial connectors |