

## Han-Modular coax F-contact 500hm (RG174)



	•	,	
	Part number		09 14 000 6211
	Specification		Han-Modular coax F-contact 50Ohm (RG174)
	HARTING eCatalog	ue	https://b2b.harting.com/09140006211

Image is for illustration purposes only. Please refer to product description.

## Identification

**REACH Annex XVII substances** 

Category Contacts   Series DIN 41626   Type of contact Coaxial contact   Description of the contact for cables RG 174 U, 188 AU, 316 U   Version Version   Termination method Solder/crimp termination   Gender Female   Manufacturing process Turned contacts   Technical characteristics \$1.5 A   Contact resistance \$10 mΩ   Impedance \$0 Ω   Material properties Copper alloy   Material (contacts) Gold plated   RoHS compliant with exemption   RoHS exemptions 6(c): Copper alloy containing up to 4 % lead by weig					
Type of contactCoaxial contactDescription of the contactfor cables RG 174 U, 188 AU, 316 UVersionVersionTermination methodSolder/crimp terminationGenderFemaleManufacturing processTurned contactsTechnical characteristicsSolder/crimp terminationRated current≤1.5 AContact resistance≤10 mQImpedance50 QMaterial propertiesCopper alloySurface (contacts)Gold platedRoHScompliant with exemptionRoHS exemptions6(c): Copper alloy containing up to 4 % lead by weight					
Description of the contact for cables RG 174 U, 188 AU, 316 U   Version Termination method Solder/crimp termination   Gender Female Impedance   Material properties ≤1.5 A Impedance   Material (contacts) Sol Q Impedance   Surface (contacts) Gold plated Gold plated   RoHS exemptions 6(c): Copper alloy containing up to 4 % lead by weight					
VersionTermination methodSolder/crimp terminationGenderFemaleManufacturing processTurned contactsTechnical characteristicsTurned contactsRated current≤1.5 AContact resistance≤10 mQImpedance50 QMaterial propertiesSolder/crimp and soldMaterial (contacts)Copper alloySurface (contacts)Gold platedRoHScompliant with exemptionRoHS exemptions6(c): Copper alloy containing up to 4 % lead by weight					
Termination methodSolder/crimp terminationGenderFemaleManufacturing processTurned contactsTechnical characteristicsTurned contactsRated current≤1.5 AContact resistance≤10 mQImpedance50 QMaterial propertiesCopper alloySurface (contacts)Gold platedRoHScompliant with exemptionRoHS exemptions6(c): Copper alloy containing up to 4 % lead by weight					
Termination methodSolder/crimp terminationGenderFemaleManufacturing processTurned contactsTechnical characteristicsTurned contactsRated current≤1.5 AContact resistance≤10 mQImpedance50 QMaterial propertiesCopper alloySurface (contacts)Gold platedRoHScompliant with exemptionRoHS exemptions6(c): Copper alloy containing up to 4 % lead by weight					
GenderFemaleManufacturing processTurned contactsTechnical characteristicsTurned contactsRated current≤1.5 AContact resistance≤10 mΩImpedance50 ΩMaterial propertiesCopper alloyMaterial (contacts)Copper alloySurface (contacts)Gold platedRoHScompliant with exemptionRoHS exemptions6(c): Copper alloy containing up to 4 % lead by weight					
Manufacturing processTurned contactsFechnical characteristicsRated current≤1.5 AContact resistance≤10 mΩImpedance50 ΩMaterial propertiesMaterial (contacts)Copper alloySurface (contacts)Gold platedRoHScompliant with exemptionRoHS exemptions6(c): Copper alloy containing up to 4 % lead by weight					
Technical characteristics   Rated current ≤1.5 A   Contact resistance ≤10 mΩ   Impedance 50 Ω   Material properties Surface (contacts)   Surface (contacts) Gold plated   RoHS compliant with exemption   RoHS exemptions 6(c): Copper alloy containing up to 4 % lead by weight					
Rated current ≤1.5 A   Contact resistance ≤10 mΩ   Impedance 50 Ω   Material properties Surface (contacts)   Contact (contacts) Copper alloy   RoHS compliant with exemption   RoHS exemptions 6(c): Copper alloy containing up to 4 % lead by weight					
Rated current ≤1.5 A   Contact resistance ≤10 mΩ   Impedance 50 Ω   Material properties Surface (contacts)   Contact (contacts) Copper alloy   RoHS compliant with exemption   RoHS exemptions 6(c): Copper alloy containing up to 4 % lead by weight					
Contact resistance ≤10 mΩ   Impedance 50 Ω   Material properties Surface (contacts)   Copper alloy Gold plated   RoHS compliant with exemption   RoHS exemptions 6(c): Copper alloy containing up to 4 % lead by weight					
Impedance50 ΩMaterial propertiesCopper alloyMaterial (contacts)Copper alloySurface (contacts)Gold platedRoHScompliant with exemptionRoHS exemptions6(c): Copper alloy containing up to 4 % lead by weight					
Material properties   Material (contacts) Copper alloy   Surface (contacts) Gold plated   RoHS compliant with exemption   RoHS exemptions 6(c): Copper alloy containing up to 4 % lead by weight					
Material (contacts)Copper alloySurface (contacts)Gold platedRoHScompliant with exemptionRoHS exemptions6(c): Copper alloy containing up to 4 % lead by weight					
Material (contacts)Copper alloySurface (contacts)Gold platedRoHScompliant with exemptionRoHS exemptions6(c): Copper alloy containing up to 4 % lead by weight					
Surface (contacts)Gold platedRoHScompliant with exemptionRoHS exemptions6(c): Copper alloy containing up to 4 % lead by weight	Material properties				
RoHScompliant with exemptionRoHS exemptions6(c): Copper alloy containing up to 4 % lead by weight					
RoHS exemptions 6(c): Copper alloy containing up to 4 % lead by weight					
	weight				
ELV status compliant with exemption					
China RoHS 50					

Page 1 / 2 | Creation date 2024-01-17 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com

Not contained



## Material properties

REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	Lead
ECHA SCIP number	b51e5b97-eeb5-438b-8538-f1771d43c17d
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead Nickel

## Specifications and approvals

Specifications	IEC 60664-1 IEC 61984			
Commercial data				
Packaging size	10			
Net weight	1 g			
Country of origin	Germany			
European customs tariff number	85366990			
GTIN	5713140018341			
ETIM	EC000796			
eCl@ss	27440204 Contact for industrial connectors			