

## Docking Frame for 4 modules, float mount




Image is for illustration purposes only. Please refer to product description.

Part number	09 14 016 1701
Specification	Docking Frame for 4 modules, float mount
HARTING eCatalogue	<a href="https://b2b.harting.com/09140161701">https://b2b.harting.com/09140161701</a>

### Identification

Category	Accessories
Series	Han-Modular®
Type of accessory	Docking frame
Description of the accessory	Float mount for 4 modules A ... D

### Technical characteristics

Limiting temperature	-40 ... +125 °C
Mating cycles	≥500
Mating cycles with other HMC components	≥10,000
Degree of protection acc. to IEC 60529	IP20
Floating tolerance	±2 mm
Lock-in range	±4 mm

### Material properties

Material	Polycarbonate (PC)
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained



**Pushing Performance**  
Since 1945

## Material properties

Fire protection on railway vehicles	EN 45545-2 (2020-08)
Requirement set with Hazard Levels	R22 (HL 1-3) R23 (HL 1-3)

## Specifications and approvals

Specifications	IEC 60664-1 IEC 61984
----------------	--------------------------

## Commercial data

Packaging size	2
Net weight	20 g
Country of origin	Germany
European customs tariff number	85389099
GTIN	5713140021112
ETIM	EC002312
eCl@ss	27440206 Module carrier frame for industrial connectors