

# Han E AV 16 Pos. M Insert Term. Block Ri



Part number	09 33 016 4636
Specification	Han E AV 16 Pos. M Insert Term. Block Ri
HARTING eCatalogue	https://b2b.harting.com/09330164636

Image is for illustration purposes only. Please refer to product description.

### Identification

Category	Inserts
Series	Han E <sup>®</sup> AV
Element	Terminal block connector
Specification	Right hand version Single contour (SK)

#### Version

Termination method	Screw termination
Gender	Male
Size	16 B
Number of contacts	16
PE contact	Yes

#### Technical characteristics

0.2 2.5 mm <sup>2</sup>
16 A
500 V
6 kV
3
600 V
>10 <sup>10</sup> Ω
≤4 mΩ
0.5 Nm



### Technical characteristics

Limiting temperature -40 ... +125 °C

Mating cycles ≥500

## Material properties

Material (insert)	Polycarbonate (PC)
Colour (insert)	RAL 7032 (pebble grey)
Material (contacts)	Copper alloy
Surface (contacts)	Silver plated
Material flammability class acc. to UL 94	V-0
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	Lead
ECHA SCIP number	5dbb3851-b94e-4e88-97a1-571845975242
California Proposition 65 substances	Yes
California Proposition 65 substances	Lead Nickel
Fire protection on railway vehicles	EN 45545-2 (2020-08)
Requirement set with Hazard Levels	R22 (HL 1-3) R23 (HL 1-3)

# Specifications and approvals

Specifications	IEC 60664-1 IEC 61984
UL / CSA	UL 1977 ECBT2.E235076
Approvals	DNV GL

#### Commercial data

Packaging size	1
Net weight	160.5 g
Country of origin	Romania

Product data sheet 09 33 016 4636 Han E AV 16 Pos. M Insert Term. Block Ri



### Commercial data

European customs tariff number	85366990
GTIN	5713140051638
ETIM	EC000438
eCl@ss	27440205 Contact insert for industrial connectors