


# Han 10HvE-F-s



| Part number        | 09 34 010 2701                      |
|--------------------|-------------------------------------|
| Specification      | Han 10HvE-F-s                       |
| HARTING eCatalogue | https://b2b.harting.com/09340102701 |

Image is for illustration purposes only. Please refer to product description.

### Identification

| Category | Inserts               |
|----------|-----------------------|
| Series   | Han Hv E <sup>®</sup> |

#### Version

| Termination method                | Screw termination |
|-----------------------------------|-------------------|
| Gender                            | Female            |
| Size                              | 24 B              |
| With wire protection              | Yes               |
| Number of contacts                | 12                |
| Number of power contacts          | 10                |
| Number of special contacts        | 2                 |
| Specification of special contacts | Relay contact     |
| PE contact                        | Yes               |

### Technical characteristics

| Conductor cross-section   | 0.75 2.5 mm²  |
|---------------------------|---------------|
| Conductor cross-section   | AWG 18 AWG 14 |
| Rated current             | 16 A          |
| Rated voltage             | 830 V         |
| Rated impulse voltage     | 8 kV          |
| Pollution degree          | 3             |
| Rated voltage acc. to UL  | 600 V         |
| Rated voltage acc. to CSA | 600 V         |



### Technical characteristics

| Insulation resistance | >10 <sup>10</sup> Ω |
|-----------------------|---------------------|
| Contact resistance    | ≤1 mΩ               |
| Stripping length      | 7.5 mm              |
| Tightening torque     | 0.5 Nm              |
| Limiting temperature  | -40 +125 °C         |
| Mating cycles         | ≥500                |

### Material properties

| Material (insert)                         | Polycarbonate (PC)  |
|---|---|
| Colour (insert)                           | RAL 7032 (pebble grey)  |
| Material (contacts)                       | Copper alloy  |
| Surface (contacts)                        | Silver plated   |
| Material flammability class acc. to UL 94 | V-0   |
| RoHS                                      | compliant with exemption  |
| RoHS exemptions                           | 6(c): Copper alloy containing up to 4 % lead by weight            |
| ELV status                                | compliant with exemption  |
| China RoHS                                | 50  |
| REACH Annex XVII substances               | Not contained   |
| REACH ANNEX XIV substances                | Not contained   |
| REACH SVHC substances                     | Yes   |
| REACH SVHC substances                     | Potassium 1,1,2,2,3,3,4,4,4-nonafluorobutane-1-sulphonate<br>Lead |
| ECHA SCIP number                          | 5dbb3851-b94e-4e88-97a1-571845975242                              |
| California Proposition 65 substances      | Yes   |
| California Proposition 65 substances      | Lead<br>Nickel  |
| Fire protection on railway vehicles       | EN 45545-2 (2020-08)  |
| Requirement set with Hazard Levels        | R26   |
|   |   |

## Specifications and approvals

| Specifications | IEC 60664-1<br>IEC 61984 |
|----------------|--------------------------|
| UL / CSA       | UL 1977 ECBT2.E235076    |



### Commercial data

| Packaging size                 | 1   |
|--------------------------------|---|
| Net weight                     | 95.82 g   |
| Country of origin              | Romania   |
| European customs tariff number | 85366990  |
| GTIN                           | 5713140053441                                     |
| eCl@ss                         | 27440205 Contact insert for industrial connectors |