

## D-Sub crimp 15-pole male assembly



Image is for illustration purposes only. Please refer to product description.

Part number	09 67 015 5601
Specification	D-Sub crimp 15-pole male assembly
HARTING eCatalogue	<a href="https://b2b.harting.com/09670155601">https://b2b.harting.com/09670155601</a>

### Identification

Category	Connectors
Series	D-Sub
Identification	Standard
Element	Connector

### Version

Termination method	Crimp termination
Gender	Male
Size	D-Sub 2
Connection type	PCB to cable Cable to cable
Number of contacts	15
Locking type	Fixing flange with feed through hole $\varnothing$ 3.1 mm
Details	Please order crimp contacts separately.

### Technical characteristics

Conductor cross-section	0.09 ... 0.82 mm <sup>2</sup>
Conductor cross-section	AWG 28 ... AWG 18
Wire outer diameter	2.4 mm
Clearance distance	$\geq$ 1 mm
Creepage distance	$\geq$ 1 mm
Insulation resistance	$>10^{10}$ $\Omega$
Limiting temperature	-55 ... +125 °C



Pushing Performance  
Since 1945

## Technical characteristics

Insertion force	≤50 N
Withdrawal force	≥4.5 N ≤33 N
Test voltage $U_{r.m.s.}$	1 kV
Isolation group	II ( $400 \leq CTI < 600$ )
Hot plugging	No

## Material properties

Material (insert)	Thermoplastic resin, glass-fibre filled (PBTP) Shell: Plated steel
Colour (insert)	Black
Material flammability class acc. to UL 94	V-0
RoHS	compliant
ELV status	compliant
China RoHS	e
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Not contained
California Proposition 65 substances	Not contained
Fire protection on railway vehicles	EN 45545-2 (2020-08)
Requirement set with Hazard Levels	R26

## Specifications and approvals

Specifications	DIN 41652 IEC 60807-3 CECC 75301-802
UL / CSA	UL 1977 ECBT2.E102079

## Commercial data

Packaging size	100
Net weight	0.54 g
Country of origin	China
European customs tariff number	85366990
GTIN	5713140090897
ETIM	EC001136



**Pushing Performance**  
Since 1945

## Commercial data

eCl@ss

27440214 D-Sub coupler