

# Han 32A-HTE/HSE-M32



Part number	19 20 032 0597
Specification	Han 32A-HTE/HSE-M32
HARTING eCatalogue	https://b2b.harting.com/19200320597

Image is for illustration purposes only. Please refer to product description.

### Identification

Category	Hoods/Housings
Series of hoods/housings	Han A <sup>®</sup>
Type of hood/housing	Hood
Туре	High construction

### Version

Size	32 A
Version	Top/side entry
Cable entry	2x M32
Locking type	Double locking lever
Field of application	Standard Hoods/housings for industrial applications

## Technical characteristics

Limiting temperature	-40 +125 °C
Note on the limiting temperature	For use as a connector according to IEC 61984.
Degree of protection acc. to IEC 60529	IP65
Type rating acc. to UL 50 / UL 50E	4
	4X
	12

### Material properties

Material (hood/housing)	Aluminium die-cast
Surface (hood/housing)	Powder-coated
Colour (hood/housing)	RAL 7037 (dust grey)



## Material properties

NBR
compliant
compliant
е
Not contained
Not contained
Not contained
EN 45545-2 (2020-08)
R1 (HL 1-3) R7 (HL 1-3)

## Specifications and approvals

Approvals	CE
	DNV GL

#### Commercial data

Packaging size	1
Net weight	189.28 g
Country of origin	Germany
European customs tariff number	85389099
GTIN	5713140164284
ETIM	EC000437
eCl@ss	27440202 Shell for industrial connectors