

## Han-Eco Mod.24-C-f. HBM/HSM/HCC



Image is for illustration purposes only. Please refer to product description.

|                    |   |
|--------------------|---|
| Part number        | 19 41 024 5405  |
| Specification      | Han-Eco Mod.24-C-f. HBM/HSM/HCC   |
| HARTING eCatalogue | <a href="https://b2b.harting.com/19410245405">https://b2b.harting.com/19410245405</a> |

### Identification

|                              |   |
|------------------------------|---|
| Category                     | Accessories   |
| Series of hoods/housings     | Han-Eco® Modular  |
| Type of accessory            | Protection cover  |
| Description of the accessory | for bulkhead mounted housings<br>for surface mounted housings<br>for cable to cable housing |

### Version

|              |                      |
|--------------|----------------------|
| Size         | 24 B                 |
| Locking type | Double locking lever |

### Technical characteristics

|  |                 |
|--|-----------------|
| Limiting temperature                   | -40 ... +125 °C |
| Number of relockings                   | ≥500            |
| Degree of protection acc. to IEC 60529 | IP65            |

### Material properties

|   |  |
|---|--|
| Material (hood/housing)                   | Polyamide (PA)<br>Fibre-glass reinforced |
| Colour (hood/housing)                     | RAL 9005 (jet black)                     |
| Material flammability class acc. to UL 94 | V-0                                      |
| RoHS                                      | compliant                                |
| ELV status                                | compliant                                |
| China RoHS                                | e  |



**Pushing Performance**  
Since 1945

## Material properties

|                                     |                              |
|-------------------------------------|------------------------------|
| REACH Annex XVII substances         | Not contained                |
| REACH ANNEX XIV substances          | Not contained                |
| REACH SVHC substances               | Not contained                |
| Fire protection on railway vehicles | EN 45545-2 (2020-08)         |
| Requirement set with Hazard Levels  | R22 (HL 1-3)<br>R23 (HL 1-3) |

## Specifications and approvals

|                |   |
|----------------|---|
| Specifications | IEC 61984<br>EN 45545-2 Fire protection on railway vehicles |
| UL / CSA       | UL 1977 ECBT2.E235076<br>CSA-C22.2 No. 182.3 ECBT8.E235076  |

## Commercial data

|                                |  |
|--------------------------------|--|
| Packaging size                 | 1                                      |
| Net weight                     | 60 g                                   |
| Country of origin              | Germany                                |
| European customs tariff number | 85389099                               |
| GTIN                           | 5713140131217                          |
| ETIM                           | EC002314                               |
| eCl@ss                         | 27440208 Cap for industrial connectors |