

## DIN 41626 female connector for 12 5Ám GI



Part number	20 10 125 4222
Specification	DIN 41626 female connector for 12 5Ám GI
HARTING eCatalogue	https://b2b.harting.com/20101254222

Image is for illustration purposes only. Please refer to product description.

## Identification

Category	Contacts
Series	DIN 41626
	har-modular <sup>®</sup>
Type of contact	FO contact
Description of the contact	for GI fibre 50/125 μm
	for ceramic ferrule 62.5/125 μm
Version	
Version	
Gender	Female
Manufacturing process	Turned contacts
Material properties	
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	Not contained
REACH ANNEX XIV substances	Not contained
REACH SVHC substances	Yes
REACH SVHC substances	Lead
ECHA SCIP number	b51e5b97-eeb5-438b-8538-f1771d43c17d
California Proposition 65 substances	Yes

Page 1 / 2 | Creation date 2024-01-17 | Please note that the data specified here were taken as extracts from the online catalogue. Please refer to the user documentation for the complete and up-to-date information and data. Please also note that the user is responsible for validating functionality, conformity with applicable laws and directives, as well as for the electrical safety in the particular application. HARTING Electric Stiftung & Co. KG | Wilhelm-Harting-Straße 1 | 32339 Espelkamp | Germany Phone +49 5772 47-97100 | electric@HARTING.com | www.HARTING.com



## Material properties

California Proposition 65 substances	Lead Nickel
Commercial data	
Packaging size	1
Net weight	7 g
Country of origin	Germany
European customs tariff number	85367000
GTIN	5713140133563
eCl@ss	27440204 Contact for industrial connectors