

SPECIFICATIONS

1. General Specifications

Model	SZL-001
Applicable Models	List in the website http://www.patlite.com/
Applicable Pole	
Mounting Location	Indoor Only
Mass (Tolerance $\pm 10\%$)	0.09kg
Outer Dimensions	Refer to the 2.Outer Dimensions
Remarks	There are no contents of controlled substances exceeding the threshold for the RoHS

2. Outer Dimensions

SZL-001
(Unit:mm)

Technical drawing of the L-bracket (SZL-001) showing front and side views with dimensions. The front view shows a horizontal arm of length 75 mm and a vertical arm of length 80 mm. The horizontal arm has a hole with diameter $\varnothing 22.5$ mm and a radius of $R20$. The vertical arm has a hole with diameter $\varnothing 9$ mm and a radius of $R20$. The thickness of the horizontal arm is 3 mm. The distance from the center of the horizontal hole to the center of the vertical hole is 55 mm. The distance from the center of the horizontal hole to the end of the horizontal arm is 20 mm. The distance from the center of the vertical hole to the end of the vertical arm is 5 mm. The vertical arm has two holes with diameter $2-\varnothing 11$ mm. The distance between the centers of these two holes is 80 mm. The distance from the center of the vertical hole to the end of the vertical arm is 20 mm. The distance from the center of the vertical hole to the center of the horizontal hole is 55 mm. The distance from the center of the vertical hole to the end of the vertical arm is 5 mm. The distance from the center of the vertical hole to the end of the vertical arm is 5 mm. The distance from the center of the vertical hole to the end of the vertical arm is 5 mm.

No.	Name	Material
1	L-bracket	SPHC-P

SZL-001-W18B-1_2

PATLITE Corporation

3.Mounting Dimensional Drawing

